Bocht 87°30 mof/mof

Productkenmerken

Het PVC-hulpstuk, 70 jaar geleden uitgevonden door Nicoll, is vandaag verkrijgbaar in meer dan 1000 uitvoeringen en vormt daarmee het breedste assortiment op de markt. Met de PVC-hulpstukken van Nicoll kunnen alle verbindingen en richtingsveranderingen worden gerealiseerd in vrijvervalsystemen voor afvalwater, in combinatie met alle buizen op de markt.

Nicoll biedt een service op maat voor alle situaties op de werf.

De bocht mof/mof maakt een richtingsverandering in het leidingnet mogelijk en is geschikt voor buizen zonder aangevormde mof. De vorm bevordert de doorstroming.

Technische beschrijving

Diameter	32 tot 315
Hoek	87'30°
Kleur	Grijs
Materiaal	PVC
Verbinding	Mof/mof

De voordelen van Nicoll: prestaties

- Productiekwaliteit: gegarandeerde stevigheid voor weerstand tegen allerlei schokken en een eenvoudige verwerking
- In combinatie met PVC-buizen van Nicoll: een complete oplossing voor een hoogwaardig en volledig waterdicht afvoersysteem
- De certificeringen NFMe en B-s1,d0 garanderen constante productprestaties en conformiteit met de normen
- Een buigstraal die zorgt voor een optimale vloeistofdoorstroming
- Hulpstukken van glad, niet-microporeus PVC: voorkomen de ophoping van verontreinigingen

De voordelen van Nicoll: installatie

- De buis schuift gemakkelijk in het hulpstuk dankzij de nauwkeurige maattoleranties
- Verstevigingsrand tegen ovaalvorming voor een eenvoudige montage
- Dankzij hun compacte uitvoering kunnen ze ook in zeer krappe ruimtes worden geïnstalleerd
- Geschikt voor buizen zonder aangevormde mof

Bocht 87°30 mof/mof

product.detail.attribute.sku	Diameter (mm)	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Weight (kg)
UCF88	32	Light grey	87°30	32	ø Raccord	PVC	Female/ Female	To be glued	0.036
CF88	32	Light grey	87°30	32	ø Raccord	PVC	Female/ Female	To be glued	0.036
CH88	40	Light grey	87°30	40	ø Raccord	PVC	Female/ Female	To be glued	0.058
UCJ88	50	Light grey	87°30	50	ø Raccord	PVC	Female/ Female	To be glued	0.074
CJ88	50	Light grey	87°30	50	ø Raccord	PVC	Female/ Female	To be glued	0.076
UCB88	200	Light grey	87°30	200	ø Raccord	PVC	Female/ Female	To be glued	1.412
CB88	200	Light grey	87°30	200	ø Raccord	PVC	Female/ Female	To be glued	1.412
CD887	-	Light grey	87°30	25	ø Raccord	PVC	Female/ Female	To be glued	2.179
CE887	-	Light grey	87°30	315	ø Raccord	PVC	Female/ Female	To be glued	4.533
UCL88	63	-	87°30	-	-	PVC	-	To be glued	0.143
C1FF	63	-	87°30	-	-	PVC	-	To be glued	0.14

Bocht 87°30 mof/mof

product.detail.attribute.sku	Diameter (mm)	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Weight (kg)
CL88	63	-	87°30	-	-	PVC	-	To be glued	0.143
UCP88	75	Light grey	87°30	75	ø Raccord	PVC	Female/ Female	To be glued	0.199
CP88	75	Light grey	87°30	75	ø Raccord	PVC	Female/ Female	To be glued	0.199
CR88	80	Light grey	87°30	80	ø Raccord	PVC	Female/ Female	To be glued	-
CT88	100	Grey	-	-	-	PVC	Female/ Female	To be glued	-
CV88	-	Light grey	87°30	110	ø Raccord	PVC	Female/ Female	To be glued	0.424
UCV88	-	Light grey	87°30	110	ø Raccord	PVC	Female/ Female	To be glued	0.424
CX88	125	Light grey	87°30	125	ø Raccord	PVC	Female/ Female	To be glued	0.655
CY88	140	Light grey	87°30	14	ø Raccord	PVC	Female/ Female	To be glued	0.722
CZ88	160	Light grey	87°30	160	ø Raccord	PVC	Female/ Female	To be glued	-
CS88	-	Grey	-	-	-	-	-	-	0.296
UCS88	-	Grey	-	-	-	-	-	-	0.296
C2FF	-	-	-	-	-	-	-	-	0.226
C32FF	-	-	-	-	-	-	-	-	0.033
C40FF	-	-	-	-	-	-	-	-	0.052
C50FF	-	-	-	-	-	-	-	-	0.091
C10FF	-	-	-	-	-	-	-	-	2.055
C5FF	-	-	-	-	-	-	-	-	0.47
C6FF	-	-	-	-	-	-	-	-	0.616
C8FF	-	-	-	-	-	-	-	-	1.28