Bocht 87°30 mof/spie

Productkenmerken

Het PVC-hulpstuk, 70 jaar geleden uitgevonden door Nicoll, is vandaag verkrijgbaar in meer dan 1000 uitvoeringen en vormt daarmee het breedste assortiment op de markt. Met de PVC-hulpstukken van Nicoll kunnen alle verbindingen en richtingsveranderingen worden gerealiseerd in vrijvervalsystemen voor afvalwater, in combinatie met alle buizen op de markt.

Nicoll biedt een ‘op maat gemaakte’ service aan om aan alle bouwconfiguraties te kunnen voldoen.

De bocht mof/spie maakt een richtingsverandering in het leidingnet mogelijk, met behoud van de stroomrichting. De vorm bevordert de doorstroming.

Technische beschrijving

Diameter	32 tot 315
Hoek	87'30°
Kleur	Grijs
Materiaal	PVC
Aansluiting	Mof/spie
Norm	NFe

De voordelen van Nicoll Performance

- Vervaardigingskwaliteit: gegarandeerde stevigheid die bestand is tegen alle soorten schokken en de installatie vergemakkelijkt
- In combinatie met Nicoll PVC-buizen: een complete oplossing voor een afvoersysteem van zeer hoge kwaliteit dat perfect waterdicht is
- De NFMe- en B-s1,d0-certificeringen garanderen de constante prestaties van de producten en hun conformiteit met de normen
- Buigradius die ervoor zorgt dat de vloeistoffen perfect worden geleid
- Hulpstukken van glad, niet-microporeus PVC: voorkomen de ophoping van verontreinigingen

De voordelen van Nicoll-installatie

- De buis schuift gemakkelijk in het hulpstuk dankzij de nauwkeurige maattoleranties
- Anti-ovalisatie-ribbel die het in elkaar steken vergemakkelijkt

Bocht 87°30 mof/spie

- Compacte uitvoering voor installatie in zeer krappe ruimtes
- Behoud van de stroomrichting

product.detail.attribute.sku	Diameter (mm)	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Weight (kg)
UCF8	32	Light grey	87°30	32	ø Raccord	PVC	Male/ Female	To be glued	0.034
CF8	32	Light grey	87°30	32	ø Raccord	PVC	Male/ Female	To be glued	0.034
UCH8	40	Light grey	87°30	40	ø Raccord	PVC	Male/ Female	To be glued	0.053
CH8	40	Light grey	87°30	40	ø Raccord	PVC	Male/ Female	To be glued	0.051
UCJ8	50	Light grey	87°30	50	ø Raccord	PVC	Male/ Female	To be glued	0.074
CJ8	50	Light grey	87°30	50	ø Raccord	PVC	Male/ Female	To be glued	0.075
CB8	200	Light grey	87°30	200	ø Raccord	PVC	Male/ Female	To be glued	1.406
CD87	-	Light grey	87°30	25	ø Raccord	PVC	Male/ Female	To be glued	2.25
CE87	-	Light grey	87°30	315	ø Raccord	PVC	Male/ Female	To be glued	4.648
UCL8	63	Light grey	87°30	-	-	PVC	Male/ Female	To be glued	0.121

Bocht 87°30 mof/spie

product.detail.attribute.sku	Diameter (mm)	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Weight (kg)
C1	63	Light grey	87°30	-	-	PVC	Male/ Female	To be glued	0.132
CL8	63	Light grey	87°30	-	-	PVC	Male/ Female	To be glued	0.121
UCP8	75	Light grey	87°30	75	ø Raccord	PVC	Male/ Female	To be glued	0.196
CP8	75	Light grey	87°30	75	ø Raccord	PVC	Male/ Female	To be glued	0.196
CR8	80	Light grey	87°30	80	ø Raccord	PVC	Male/ Female	To be glued	-
CT8	100	Grey	-	-	-	PVC	Male/ Female	To be glued	-
CV8	110	Light grey	87°30	110	ø Raccord	PVC	Male/ Female	To be glued	0.422
UCV8	110	Light grey	87°30	110	ø Raccord	PVC	Male/ Female	To be glued	0.422
CX8	125	Light grey	87°30	125	ø Raccord	PVC	Male/ Female	To be glued	-
CY8	-	Light grey	87°30	14	ø Raccord	PVC	Male/ Female	To be glued	0.686
UCY8	-	Light grey	87°30	14	ø Raccord	PVC	Male/ Female	To be glued	0.686
CZ8	160	Light grey	87°30	160	ø Raccord	PVC	Male/ Female	To be glued	-
CS8	90	Grey	-	-	-	-	-	-	0.296
UCS8	90	Grey	-	-	-	-	-	-	0.296
C3	90	Grey	-	-	-	-	-	-	0.239
C2	-	-	-	-	-	-	-	-	0.225
XC4	-	-	-	-	-	-	-	-	0.34
C5	-	-	-	-	-	-	-	-	0.454
XC32	-	-	-	-	-	-	-	-	0.03
XC6	-	-	-	-	-	-	-	-	0.605
XC40	-	-	-	-	-	-	-	-	0.05
C50GIR	-	-	-	-	-	-	-	-	0.088
C10	-	-	-	-	-	-	-	-	2.026
C8	-	-	-	-	-	-	-	-	1.263