

Excentrisch verloopstuk mof/spie, enkel

○ Productkenmerken

Het PVC-hulpstuk, 70 jaar geleden uitgevonden door Nicoll, is vandaag verkrijgbaar in meer dan 1000 uitvoeringen en vormt daarmee het breedste assortiment op de markt. Met de PVC-hulpstukken van Nicoll kunnen alle verbindingen en richtingsveranderingen worden gerealiseerd in vrijvervalsysteem voor afvalwater, in combinatie met alle buizen op de markt.

Nicoll biedt een 'op maat gemaakte' service aan om aan alle bouwconfiguraties te kunnen voldoen.

Het enkelvoudige verloopstuk mof/spie maakt het mogelijk de aansluitdiameter van een toestel te verkleinen, met behoud van de stroomrichting.

○ Technische beschrijving

Diameter	32 à 125
Kleur	Grijs
Materiaal	PVC
Aansluiting	Mof/spie
Norm	NFe

De voordelen van Nicoll Performance

- Productiekwaliteit: gegarandeerde stevigheid voor weerstand tegen allerlei schokken en een eenvoudige verwerking
- In combinatie met Nicoll PVC-buizen: een complete oplossing voor een afvoersysteem van zeer hoge kwaliteit dat perfect waterdicht is
- De NFMe- en B-s1,d0-certificeringen garanderen de constante prestaties van de producten en hun conformiteit met de normen
- Hulpstukken van glad, niet-microporeus PVC: voorkomen de ophoping van verontreinigingen

De voordelen van Nicoll-installatie

- De buis schuift gemakkelijk in het hulpstuk dankzij de nauwkeurige maattoleranties
- Anti-ovalisatie-ribbel die het in elkaar steken vergemakkelijkt
- Reductie ingebouwd in de insteeklengte
- Draaibaar onderdeel voor afstelling op de werf
- Ruim assortiment aansluitdiameters
- Behoudt de stroomrichting

Excentrisch verloopstuk mof/spie, enkel



product.detail.attribute.sku	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Height (mm)	Diameter 1 label	Diameter 2 label	Material	Type	Assembly type	DN1 mm	DN mm	Weight (kg)
L3	Indoor	Light grey	63	32	38.5	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.051
XTR63/40	Indoor	Light grey	-	4	38	-	ø d	PVC	Single	To be glued	-	-	0.05
L4	Indoor	Light grey	-	4	38	-	ø d	PVC	Single	To be glued	-	-	0.05
TR63/50	Indoor	Light grey	-	5	38	-	ø d	PVC	Single	To be glued	-	-	0.06
XTR63/50	Indoor	Light grey	-	5	38	-	ø d	PVC	Single	To be glued	-	-	0.06
L5	Indoor	Light grey	-	5	38	-	ø d	PVC	Single	To be glued	-	-	0.059
UP3	Indoor	Light grey	75	32	44.5	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.07
P3	Indoor	Light grey	75	32	44.5	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.07
UP4	Indoor	Light grey	-	4	44	-	ø d	PVC	Male/ Female	To be glued	-	-	0.069
P4	Indoor	Light grey	-	4	44	-	ø d	PVC	Male/ Female	To be glued	-	-	0.069
UP5	Indoor	Light grey	-	5	44	-	ø Raccord	PVC	Male/ Female	To be glued	-	-	0.074

Excentrisch verloopstuk mof/spie, enkel

product.detail.attribute.sku	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Height (mm)	Diameter 1 label	Diameter 2 label	Material	Type	Assembly type	DN1 mm	DN2 mm	Weight (kg)
P5	Indoor	Light grey	-	5	44	-	ø Raccord	PVC	Male/ Female	To be glued	-	-	0.074
TR75/63	Indoor	Light grey	75	63	44	-	ø d	PVC	Male/ Female	To be glued	-	-	0.078
UP6	Indoor	Light grey	75	63	44	-	ø d	PVC	Male/ Female	To be glued	-	-	0.077
P6	Indoor	Light grey	75	63	44	-	ø d	PVC	Male/ Female	To be glued	-	-	0.077
R3	Indoor	Light grey	80	32	47	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.072
UR3	Indoor	Light grey	80	32	47	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.072
R4	Indoor	Light grey	8	4	47	-	ø d	PVC	-	To be glued	-	-	0.074
TR80/40	Indoor	Light grey	8	4	47	-	ø d	PVC	-	To be glued	-	-	0.075
UR4	Indoor	Light grey	8	4	47	-	ø d	PVC	-	To be glued	-	-	0.075
XTR80/40	Indoor	Light grey	8	4	47	-	ø d	PVC	-	To be glued	-	-	0.075
R5	Indoor	Light grey	-	5	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.078
TR80/50	Indoor	Light grey	-	5	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.078
UR5	Indoor	Light grey	-	5	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.078
R6	Indoor	Light grey	-	63	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.083
TR80/63	Indoor	Light grey	-	63	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.084
UR6	Indoor	Light grey	-	63	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.083
XTR80/63	Indoor	Light grey	-	63	47	-	ø d	PVC	Male/ Female	To be glued	-	-	0.084
S3	Indoor	Light grey	-	32	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.092
S4	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.093
TR90/40	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.095
US4	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.093

Excentrisch verloopstuk mof/spie, enkel

product.detail.attribute.sku	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Height (mm)	Diameter 1 label	Diameter 2 label	Material	Type	Assembly type	DN1 mm	DN mm	Weight (kg)
S5	Indoor	Light grey	-	5	-	-	ø d	PVC	Single	To be glued	-	-	0.097
US5	Indoor	Light grey	-	5	-	-	ø d	PVC	Single	To be glued	-	-	0.097
S6	Indoor	Light grey	-	63	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.102
US6	Indoor	Light grey	-	63	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.102
S7	Indoor	Light grey	90	75	52	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.102
US7	Indoor	Light grey	90	75	52	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.102
S8	Indoor	Light grey	-	8	52	-	ø d	PVC	Male/Female	To be glued	-	-	0.095
US8	Indoor	Light grey	-	8	52	-	ø d	PVC	Male/Female	To be glued	-	-	0.095
T4	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.12
T5	Indoor	Light grey	100	50	-	ø D	ø d	PVC	Single	To be glued	-	-	0.114
UT5	Indoor	Light grey	100	50	-	ø D	ø d	PVC	Single	To be glued	-	-	0.114
T8	Indoor	Light grey	100	80	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.113
UT8	Indoor	Light grey	100	80	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.113
UV10	Indoor	Light grey	110	100	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.138
V10	Indoor	Light grey	110	100	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.137
V6	Indoor	Light grey	110	63	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.16
UV7	Indoor	Light grey	-	75	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.169
V7	Indoor	Light grey	-	75	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.169
UV8	Indoor	Light grey	110	80	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.17
V8	Indoor	Light grey	110	80	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.17
UV9	Indoor	Light grey	-	9	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.156

Excentrisch verloopstuk mof/spie, enkel

product.detail.attribute.sku	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Height (mm)	Diameter 1 label	Diameter 2 label	Material	Type	Assembly type	DN1 mm	DN2 mm	Weight (kg)
V9	Indoor	Light grey	-	9	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.156
UX11	Indoor	Light grey	-	11	-	-	ø D	PVC	Male/ Female	To be glued	-	-	0.232
X11	Indoor	Light grey	-	11	-	-	ø D	PVC	Male/ Female	To be glued	-	-	0.23
X3	Indoor	Light grey	125	32	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.19
UX4	Indoor	Light grey	125	40	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.179
X4	Indoor	Light grey	125	40	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.179
X5	Indoor	Light grey	125	50	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.175
UX6	Indoor	Light grey	-	63	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.18
X6	Indoor	Light grey	-	63	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.18
UX7	Indoor	Light grey	125	75	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.189
X7	Indoor	Light grey	125	75	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.189
X8	Indoor	Light grey	125	80	-	ø D	ø d	PVC	Male/ Female	To be glued	-	-	0.187
UX9	Indoor	Light grey	-	9	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.195
X9	Indoor	Light grey	-	9	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.195
T3	Indoor	Light grey	-	32	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.107
TR100/32	Indoor	Light grey	-	32	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.109
UT3	Indoor	Light grey	-	32	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.109
TR100/40	-	-	-	-	-	-	-	-	-	-	-	-	0.092
TR100/50	-	-	-	-	-	-	-	-	-	-	-	-	0.102
TR100/80	-	-	-	-	-	-	-	-	-	-	-	-	0.114
TR80/32	-	-	-	-	-	-	-	-	-	-	-	-	0.091
UX10	Indoor	Light grey	-	1	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.166
X10	Indoor	Light grey	-	1	-	-	ø d	PVC	Male/ Female	To be glued	-	-	0.174

Excentrisch verloopstuk mof/spie, enkel

product.detail.attribute.sku	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Height (mm)	Diameter 1 label	Diameter 2 label	Material	Type	Assembly type	DN1 mm	DN mm	Weight (kg)
XTR80/75	-	-	-	-	-	-	-	-	-	-	-	-	0.045
TR5/4	-	-	-	-	-	-	-	-	-	-	-	-	0.135
XTR5/4	-	-	-	-	-	-	-	-	-	-	-	-	0.135
T9	Indoor	Light grey	1	9	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.114
TR100/90	Indoor	Light grey	1	9	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.115
UT9	Indoor	Light grey	1	9	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.113
T7	Indoor	Light grey	-	75	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.134
TR100/75	Indoor	Light grey	-	75	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.13
UT7	Indoor	Light grey	-	75	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.134
UV4	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.159
V4	Indoor	Light grey	-	4	-	-	ø d	PVC	Male/Female	To be glued	-	-	0.157
TR90/80	-	-	-	-	-	-	-	-	-	-	-	-	0.095
V3	Indoor	Light grey	11	32	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.155
UV5	Indoor	Light grey	11	5	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.16
V5	Indoor	Light grey	11	5	-	ø D	ø d	PVC	Male/Female	To be glued	-	-	0.159