

PM-PMEVREDEEMF

○ Productkenmerken

Het PVC-hulpstuk, 70 jaar geleden uitgevonden door Nicoll, is vandaag verkrijgbaar in meer dan 1000 uitvoeringen en vormt daarmee het breedste assortiment op de markt. Met de PVC-hulpstukken van Nicoll kunnen alle verbindingen en richtingsveranderingen worden gerealiseerd in vrijvervalsystemen voor afvalwater, in combinatie met alle buizen op de markt.

Nicoll biedt een 'op maat gemaakte' service aan om aan alle bouwconfiguraties te kunnen voldoen.

De uitwendige excentrische reductie mof/spie maakt een verkleining van de doorsnede met één of meerdere diameterstappen mogelijk, met behoud van de stroomrichting.

○ Technische beschrijving

Diameter	32 tot 315
Kleur	Grijs
Materiaal	PVC
Aansluiting	Mof/spie
Norm	NFe

De voordelen van Nicoll Performance

- Productiekwaliteit: gegarandeerde stevigheid voor weerstand tegen allerlei schokken en een eenvoudige verwerking
- In combinatie met Nicoll PVC-buizen: een complete oplossing voor een afvoersysteem van zeer hoge kwaliteit dat perfect waterdicht is
- De NFMe- en B-s1,d0-certificeringen garanderen de constante prestaties van de producten en hun conformiteit met de normen
- Hulpstukken van glad, niet-microporeus PVC: voorkomen de ophoping van verontreinigingen

De voordelen van Nicoll-installatie

- De buis schuift gemakkelijk in het hulpstuk dankzij de nauwkeurige maattoleranties
- Anti-ovalisatie-ribbel die het in elkaar steken vergemakkelijkt
- Afgeknotte kegelvorm om de stroomsnelheid van het water te verhogen

PM-PMEVREDEEMF



product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
UIH1	40	32	10	-	Ø40-32	Indoor	Light grey	40	32	Ø Raccord	Ø Raccord
IH1	40	32	10	-	Ø40-32	Indoor	Light grey	40	32	Ø Raccord	Ø Raccord
UIJ1	50	40	10	-	Ø40 - 50	Indoor	Light grey	50	40	Ø Raccord	Ø Raccord
IJ1	50	40	10	-	Ø40 - 50	Indoor	Light grey	50	40	Ø Raccord	Ø Raccord
UIJ2	50	32	10	-	Ø32-50	Indoor	Light grey	50	32	Ø Raccord	Ø Raccord
IJ2	50	32	10	-	Ø32-50	Indoor	Light grey	50	32	Ø Raccord	Ø Raccord
IB1	200	160	-	-	-	Indoor	Light grey	200	160	Ø Raccord	Ø Raccord
IB3	200	125	-	-	-	Indoor	Light grey	200	125	Ø Raccord	Ø Raccord
IB4	200	110	-	-	-	Indoor	Light grey	2	11	Ø Raccord	Ø Raccord
R250/200	-	-	-	-	-	Indoor	Light grey	25	2	Ø Raccord	Ø Raccord
ID2	-	-	-	-	-	Indoor	Light grey	25	2	Ø Raccord	Ø Raccord

PM-PMEVREDEEMF

product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
ID3	-	-	-	-	-	Indoor	Light grey	250	160	ø Raccord	ø Raccord
ID5	-	-	-	-	-	Indoor	Light grey	250	125	ø Raccord	ø Raccord
ID6	-	-	-	-	-	Indoor	Light grey	250	110	ø Raccord	ø Raccord
ID7	-	-	-	-	-	Indoor	Light grey	250	100	ø Raccord	ø Raccord
IE1	-	-	-	-	-	Indoor	Light grey	-	25	-	ø Raccord
IE3	-	-	-	-	-	Indoor	Light grey	-	2	-	ø Raccord
IE4	-	-	-	-	-	Indoor	Light grey	315	160	ø Raccord	ø Raccord
IL1	63	50	-	-	-	Indoor	Light grey	-	5	-	ø Raccord
IL2	63	40	-	-	-	Indoor	Light grey	-	4	-	ø Raccord
IL3	-	-	-	-	-	Indoor	Light grey	-	32	-	ø Raccord
IP1	75	63	-	-	-	Indoor	Light grey	75	63	-	ø Raccord
IP2	75	50	-	-	-	Indoor	Light grey	75	50	ø Raccord	ø Raccord
UIP3	75	40	60	-	Ø40 - 75	Indoor	Light grey	75	40	ø Raccord	ø Raccord
IP3	75	40	60	-	Ø40 - 75	Indoor	Light grey	75	40	ø Raccord	ø Raccord
IP4	-	-	-	-	-	Indoor	Light grey	75	32	ø Raccord	ø Raccord
IR1	80	75	-	-	-	Indoor	Light grey	8	75	ø Raccord	ø Raccord
UIR2	80	63	-	-	-	Indoor	Light grey	-	63	-	ø Raccord
IR2	80	63	-	-	-	Indoor	Light grey	-	63	-	ø Raccord
UIR3	80	50	-	-	-	Indoor	Light grey	-	5	-	ø Raccord
IR3	80	50	-	-	-	Indoor	Light grey	-	5	-	ø Raccord
UIR4	-	-	-	-	-	Indoor	Light grey	80	40	ø Raccord	ø Raccord

PM-PMEVREDEEMF

product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
IR4	-	-	-	-	-	Indoor	Light grey	80	40	ø Raccord	ø Raccord
UIR5	-	-	-	-	-	Indoor	Light grey	80	32	ø Raccord	ø Raccord
IR5	-	-	-	-	-	Indoor	Light grey	80	32	ø Raccord	ø Raccord
UIS1	-	-	-	-	-	Indoor	Light grey	-	8	-	ø Raccord
IS1	-	-	-	-	-	Indoor	Light grey	-	8	-	ø Raccord
R90/75	-	-	35	-	Ø75 - 90	Indoor	Light grey	-	75	-	ø Raccord
UIS2	-	-	35	-	Ø75 - 90	Indoor	Light grey	-	75	-	ø Raccord
IS2	-	-	35	-	Ø75 - 90	Indoor	Light grey	-	75	-	ø Raccord
UIS3	-	-	-	-	-	Indoor	Light grey	90	63	ø Raccord	ø Raccord
IS3	-	-	-	-	-	Indoor	Light grey	90	63	ø Raccord	ø Raccord
R90/50	-	-	35	-	Ø50 - 90	Indoor	Light grey	9	5	ø Raccord	ø Raccord
IS4	-	-	35	-	Ø50 - 90	Indoor	Light grey	9	5	ø Raccord	ø Raccord
IS5	-	-	-	-	-	Indoor	Light grey	90	40	ø Raccord	ø Raccord
UIS6	-	-	-	-	-	Indoor	Light grey	90	32	ø Raccord	ø Raccord
IS6	-	-	-	-	-	Indoor	Light grey	90	32	ø Raccord	ø Raccord
IT1	100	90	-	-	-	Indoor	Light grey	-	9	-	ø Raccord
UIT2	100	80	-	-	-	Indoor	Light grey	100	80	ø Raccord	ø Raccord
IT2	100	80	-	-	-	Indoor	Light grey	100	80	ø Raccord	ø Raccord
IT3	100	75	-	-	-	Indoor	Light grey	1	75	ø Raccord	ø Raccord
UIT4	-	-	-	-	-	Indoor	Light grey	-	63	-	ø Raccord
IT4	-	-	-	-	-	Indoor	Light grey	-	63	-	ø Raccord

PM-PMEVREDEEMF

product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
UIT5	100	50	-	-	-	Indoor	Light grey	-	5	-	ø Raccord
IT5	100	50	-	-	-	Indoor	Light grey	-	5	-	ø Raccord
UIT6	-	-	-	-	-	Indoor	Light grey	100	40	ø Raccord	ø Raccord
IT6	-	-	-	-	-	Indoor	Light grey	100	40	ø Raccord	ø Raccord
IT7	-	-	-	-	-	Indoor	Light grey	100	32	ø Raccord	ø Raccord
IV1	110	100	-	-	-	Indoor	Light grey	110	100	ø Raccord	ø Raccord
IV2	110	90	40	-	Ø90 - 110	Indoor	Light grey	-	9	-	ø Raccord
IV3	110	80	-	-	-	Indoor	Light grey	-	8	-	ø Raccord
IV4	110	75	-	-	-	Indoor	Light grey	110	75	ø Raccord	ø Raccord
IV5	-	-	-	-	-	Indoor	Light grey	100	63	ø Raccord	ø Raccord
IV6	110	50	-	-	-	Indoor	Light grey	110	50	ø Raccord	ø Raccord
IV7	-	-	-	-	-	Indoor	Light grey	110	40	ø Raccord	ø Raccord
IV8	-	-	-	-	-	Indoor	Light grey	110	32	ø Raccord	ø Raccord
UIX1	125	110	-	-	-	Indoor	Light grey	125	110	ø Raccord	ø Raccord
IX1	125	110	-	-	-	Indoor	Light grey	125	110	ø Raccord	ø Raccord
UIX2	125	100	-	-	-	Indoor	Light grey	125	100	ø Raccord	ø Raccord
IX2	125	100	-	-	-	Indoor	Light grey	125	100	ø Raccord	ø Raccord
UIX3	125	90	35	-	Ø90 - 125	Indoor	Light grey	125	90	ø Raccord	ø Raccord
IX3	125	90	35	-	Ø90 - 125	Indoor	Light grey	125	90	ø Raccord	ø Raccord
UIX4	125	80	-	-	-	Indoor	Light grey	125	8	ø Raccord	ø Raccord
IX4	125	80	-	-	-	Indoor	Light grey	125	8	ø Raccord	ø Raccord

PM-PMEVREDEEMF

product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
IX5	125	75	35	-	Ø75 - 125	Indoor	Light grey	125	75	Ø Raccord	Ø Raccord
IX6	-	-	-	-	-	Indoor	Light grey	125	63	Ø Raccord	Ø Raccord
IX7	125	50	-	-	-	Indoor	Light grey	125	50	Ø Raccord	Ø Raccord
IX8	-	-	-	-	-	Indoor	Light grey	125	40	Ø Raccord	Ø Raccord
IX9	-	-	-	-	-	Indoor	Light grey	125	32	Ø Raccord	Ø Raccord
R140/125	-	-	-	-	-	Indoor	Light grey	14	125	Ø Raccord	Ø Raccord
IY1	-	-	-	-	-	Indoor	Light grey	14	125	Ø Raccord	Ø Raccord
UIY2	-	-	-	-	-	Indoor	Light grey	14	11	Ø Raccord	Ø Raccord
IY2	-	-	-	-	-	Indoor	Light grey	14	11	Ø Raccord	Ø Raccord
UIY3	-	-	-	-	-	Indoor	Light grey	14	1	Ø Raccord	Ø Raccord
IY3	-	-	-	-	-	Indoor	Light grey	14	1	Ø Raccord	Ø Raccord
UIZ1	160	140	-	-	-	Indoor	Light grey	16	14	Ø Raccord	Ø Raccord
IZ1	160	140	-	-	-	Indoor	Light grey	16	14	Ø Raccord	Ø Raccord
UIZ2	160	125	-	-	-	Indoor	Light grey	160	125	Ø Raccord	Ø Raccord
IZ2	160	125	-	-	-	Indoor	Light grey	160	125	Ø Raccord	Ø Raccord
IZ3	160	110	-	-	-	Indoor	Light grey	160	110	Ø Raccord	Ø Raccord
UIZ4	160	100	-	-	-	Indoor	Light grey	160	100	Ø Raccord	Ø Raccord
IZ4	160	100	-	-	-	Indoor	Light grey	160	100	Ø Raccord	Ø Raccord
R110/100	-	-	-	-	-	-	-	-	-	-	-
R110/40	-	-	-	-	-	-	-	-	-	-	-
R110/50	-	-	-	-	-	-	-	-	-	-	-
R110/75	-	-	-	-	-	-	-	-	-	-	-
R75/40	-	-	-	-	-	-	-	-	-	-	-
R75/50	-	-	-	-	-	-	-	-	-	-	-

PM-PMEVREDEEMF

product.detail.attribute.sku	diameterD	Diameter D	boxUnits	characteristics	measurement	Application	Colour	Diameter 1 (mm)	Diameter 2 (mm)	Diameter 1 label	Diameter 2 label
R90/63	-	-	-	-	-	-	-	-	-	-	-
XR100/80	-	-	-	-	-	-	-	-	-	-	-
R125/110	-	-	-	-	-	-	-	-	-	-	-
XR6/5	-	-	-	-	-	-	-	-	-	-	-
R160/125	-	-	-	-	-	-	-	-	-	-	-
R200/125	-	-	-	-	-	-	-	-	-	-	-
R200/160	-	-	-	-	-	-	-	-	-	-	-
XR6/4	-	-	-	-	-	-	-	-	-	-	-