Kruisstuk 45° mof/spie

Productkenmerken

Het PVC-hulpstuk, 70 jaar geleden uitgevonden door Nicoll, is vandaag verkrijgbaar in meer dan 1000 uitvoeringen en vormt daarmee het breedste assortiment op de markt. Met de PVC-hulpstukken van Nicoll kunnen alle verbindingen en richtingsveranderingen worden gerealiseerd in vrijvervalsystemen voor afvalwater, in combinatie met alle buizen op de markt.

Nicoll biedt een ‘op maat gemaakte’ service aan om aan alle bouwconfiguraties te kunnen voldoen.

Het parallelle kruisstuk mof/spie maakt de aansluiting van leidingen op verzamelleidingen of standleidingen mogelijk, met behoud van de stroomrichting.

Technische beschrijving

Diameter	32 à 125
Hoek	45°
Kleur	Grijs
Materiaal	PVC
Aansluiting	Mof/spie
Norm	NFe

De voordelen van Nicoll Performance

- Productiekwaliteit: gegarandeerde stevigheid voor weerstand tegen allerlei schokken en een eenvoudige verwerking
- In combinatie met Nicoll PVC-buizen: een complete oplossing voor een afvoersysteem van zeer hoge kwaliteit dat perfect waterdicht is
- De NFMe- en B-s1,d0-certificeringen garanderen de constante prestaties van de producten en hun conformiteit met de normen
- Hulpstukken van glad, niet-microporeus PVC: voorkomen de ophoping van verontreinigingen
- Een buigstraal die de vloeistofdoorstroming bevordert

De voordelen van Nicoll-installatie

- De buis schuift gemakkelijk in het hulpstuk dankzij de nauwkeurige maattoleranties
- Anti-ovalisatie-ribbel die het in elkaar steken vergemakkelijkt

Kruisstuk 45° mof/spie

- Ruim assortiment aansluitdiameters
- Ideaal voor installatie langs de muur
- Behoudt de stroomrichting

product.detail.attribute.sku	Application	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Positioning	DN1 mm	DN mm	boxUnits	cha
RF14	Indoor	Light grey	45°	32	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RH14	Indoor	Light grey	45°	40	ø Raccord	PVC	Double	To be glued	Parallel	-	-	40	-
RJ14	Indoor	Light grey	45°	50	ø Raccord	PVC	Double	To be glued	Parallel	-	-	20	-
RJ24	Indoor	Light grey	45°	50	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RL14	Indoor	Light grey	45°	63	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RL44	Indoor	Light grey	45°	63	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RP14	Indoor	Light grey	45°	75	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RP44	Indoor	Light grey	45°	75	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RR14	Indoor	Light grey	45°	80	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-

Kruisstuk 45° mof/spie

product.detail.attribute.sku	Application	Colour	Angle (degrees)	Diameter 1 (mm)	Diameter 1 label	Material	Type	Assembly type	Positioning	DN1 mm	DN mm	boxUnits	cha
RR44	Indoor	Light grey	45°	80	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RS14	Indoor	Light grey	45°	90	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RT14	Indoor	Light grey	-	-	-	PVC	Double	To be glued	Parallel	-	-	-	-
RT44	Indoor	Light grey	45°	100	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RT64	Indoor	Light grey	45°	100	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RT74	Indoor	Light grey	45°	100	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RV14	Indoor	Light grey	45°	11	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
CD110	Indoor	Light grey	45°	11	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RV24	Indoor	Light grey	45°	110	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RV74	Indoor	Light grey	45°	110	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RX34	Indoor	Light grey	45°	125	ø Raccord	PVC	Double	To be glued	-	-	-	-	-
RX84	Indoor	Light grey	45°	125	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-
RX14	Indoor	Light grey	45°	125	ø Raccord	PVC	Double	To be glued	Parallel	-	-	-	-